



























Laser head

Brand: [Brand] Focus adjmt: [Focus adjmt]

ing mode: Incremental Mode

Model: RS03/06/12/20/40/60K-CAT

Motor direction: Positive

0.60m/min

10.00mm

Back Distance: 40.00mm

Coordinates at back board: 0.00

Back limit range: -32.00 - 32.00 mm

Focus control port/se: Node 5:调焦Axis

Use Other Drive

Restore def

Manual Speed

Speed: 0.30m/min

Manual feed: 0.60m/min

Auto Speed

Speed: 6.00m/min

Acceleration: 1500.00mm/s²

Acc time: 100ms

OpticalRatioAndVer

Version: 2.02

OpticalRa... (1)100:200

ViewFirmwareVerAndCheckPar

Gas Pressure Parameter Setting

Ar test gas

Deviation allowable... 70.00 % Deviation allowable... 20.00 %

High pressure alarm: 2000.00

Low pressure alarm: 200.00

Scattered light alarm设置

Scattered light

High pressure alarm: 1950.00

High pressure alarm: 200.00

High pressure alarm: 200.00

DewPointAlarmSet

Dew point alarm

Cavity Alarm Temperature Setting

Cavity alarm

Cavity alarm: 40.00

Cavity alarm: 50.00



